







## Speed, Performance, Value - The Right Balance

- 4 Weighing units (kg, g, lb, oz)
- Colour coded keys
- Hold function
- Full range tare
- Zero Tracking
- Kg/ lb/ oz/ lb & oz switchable
- Large backlit LCD display
- Colour coded, sealed keypad
- Four load cell construction
- Wall mount bracket
- Large stainless steel platform
- Modern low profile design
- Splashproof to protect from accidental spills
- Simple 4 button operation
- Tare function
- Non-slip adjustable levelling feet
- Rechargeable battery / mains adapter supplied as standard
- Wheels to allow easy movement
- RS-232 bi-directional interface
- External calibration
- Rechargeable battery
- Auto sleep / power down function to save battery life
- Low battery indication
- DC Adapter
- Animal / dynamic weighing
- Weighing



## Technical Specifications

Model	CPWplus 35L	CPWplus 75L	CPWplus 150L	CPWplus 200L	CPWplus 300L
Maximum capacity	35kg	75kg	150kg	200kg	300kg
Readability	10g	20g	50g	50g	100g
Tare range	Full	Full	Full	Full	Full
Repeatability (S.D.)	10g	20g	50g	50g	100g
Linearity ( $\pm$ )	20g	40g	100g	100g	200g
Platform size	900 x 600mm				

## General Specifications

Units of measurement	Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Typical stabilisation time	2-3 Sec
Interface	RS-232 bi-directional Interface
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 22mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Operating temperature	0° 40°C
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Overall dimensions (wxdxh)	900 x 600 x 80mm
Dimensions notes	Indicator: 220 x 95 x 43mm (w x d x h)
Net weight	14.4kg

## Key Accessories

- RS-232 to PC Cable
- AdamDU - Data Collection Program
- ATP Thermal Printer



Adam Equipment - offices worldwide

[www.adamequipment.com](http://www.adamequipment.com)