

Pi Measure

Product specification



Standard Specification

MADE IN JAPN

Housing

without case, but only π M-100, π M-100S, π M-200, π M-200S
 π M-300, π M-300S are each in a special Aluminum case

Tension

Standard tension : 10N at 20°C

Graduation

Diameter tape is calibrated by 0.2mm, and Circumference tape by 1.0mm

Tape Width

7.0mm(Reading Part : 14mm)

Tape Thickness

0.1mm

Tape material

Black Steel tape
Tape Material:SK-85

Note

π M-31S·31S II , π M-51S·51S II , π M-100S, π M-200S, π M-300S : Diameter Calibration only
1-31,51,100,200,300 : Both Diameter and Circumference Calibration

Model numbers

Model No.	Measurement Range(Diameter)	Measurement Range(Circumference)	Remark
π M- 31S	30mm - 100mm	N/A (Not Available)	
π M- 31S II	30mm - 100mm	N/A (Not Available)	Different direction
π M- 31	30mm - 100mm	100mm - 310mm	
π M- 51S	30mm - 160mm	N/A (Not Available)	
π M- 51S II	30mm - 160mm	N/A (Not Available)	Different direction
π M- 51	30mm - 160mm	100mm - 510mm	
π M-100	30mm - 330mm	100mm - 1000mm	With Case
π M-200	30mm - 650mm	100mm - 2000mm	With Case
π M-300	30mm - 1000mm	100mm - 3000mm	With Case
π M-100S	30mm - 330mm	N/A (Not Available)	With Case
π M-200S	30mm - 650mm	N/A (Not Available)	With Case
π M-300S	30mm - 1000mm	N/A (Not Available)	With Case