

## Optional accessories

Shown mounted on stand using bracket



Mounting bracket  
No.04AZB157

For details of Special-order Products,  
refer to page C-49.

## SPECIFICATIONS

Metric					
Order No.	Range	Resolution	Accuracy*1	Optional Accessories*2	
				Extension rod	SPC cable
468-161	6 - 8mm	0.001mm	±2µm (within 2µm)	952322 (100mm)	05CZA662 (1m)  05CZA663 (2m)
468-162	8 - 10mm				
468-163	10 - 12mm				
468-164	12 - 16mm				
468-165	16 - 20mm				
468-166	20 - 25mm				
468-167	25 - 30mm		±3µm (within 3µm)	952622 (150mm)	
468-168	30 - 40mm				
468-169	40 - 50mm				
468-170	50 - 63mm				
468-171	62 - 75mm				
468-172	75 - 88mm				
468-173	87 - 100mm		±5µm (within 5µm)	952623 (150mm)	
468-174	100 - 125mm				
468-175	125 - 150mm				
468-176	150 - 175mm				
468-177	175 - 200mm				
468-178	200 - 225mm				
468-179	225 - 250mm				
468-180	250 - 275mm				
468-181	275 - 300mm				

\*1 Excluding quantizing error.

Accuracy: values measured with the entire measuring face.

Maximum difference: differences between the maximum and minimum values.

\*2 Setting ring and extension rod: optional.

\* It is not advisable to use measuring heads other than as supplied as a standard accessory, or widen a measuring range by using any other multiple sub-measuring heads. (The measuring accuracy in such cases is not guaranteed.)

Inch/Metric						
Order No.	Range	Resolution	Accuracy*1	Optional Accessories*2		
				Extension rod	SPC cable	
468-261	.275" - .35"	.00005" / 0.001mm	±.0001" (within .0001")	952322 (100mm)	05CZA662 (1m)  05CZA663 (2m)	
468-262	.35" - .425"					
468-263	.425" - .5"					
468-264	.5" - .65"					
468-265	.65" - .8"					
468-266	.8" - 1"					
468-267	1" - 1.2"		±.00015" (within .00015")	952622 (150mm)		
468-268	1.2" - 1.6"					
468-269	1.6" - 2"					
468-270	2" - 2.5"					
468-271	2.5" - 3"					
468-272	3" - 3.5"					
468-273	3.5" - 4"		.0001" / 0.001mm	±.00025" (within .00025")		952623 (150mm)
468-274	4" - 5"					
468-275	5" - 6"					
468-276	6" - 7"					
468-277	7" - 8"					
468-278	8" - 9"					
468-279	9" - 10"					
468-280	10" - 11"					
468-281	11" - 12"					

\*1 Excluding quantizing error.

Accuracy: values measured across the entire measuring face.

Maximum difference: differences between the maximum and minimum values.

\*2 Setting ring and extension rod: optional.

\* It is not advisable to use measuring heads other than as supplied as a standard accessory, or widen a measuring range by using any other multiple sub-measuring heads. (The measuring accuracy in such cases is not guaranteed.)



Interchangeable-Head Sets (interchangeable  
measuring heads type)

\* For details, refer to page C-5.



Non-interchangeable-Head Sets

\*\* For details, refer to page C-6.