


IP Codes (series 342-271-30, 342-371-30)

Level 6: Dust-proof.


No ingress of dust allowed.

Level 5: Protected against water jets.


Water projected in jets against the enclosure from any direction shall have no harmful effects.



342-271-30, 342-371-30, 112-401



342-451



142-402, 142-403

Battery for series 342

SR44 (1 pc), 938882, for initial operational checks (standard accessory)

Battery life: Approx. 2.4 years under normal use (for series 342-271-30/342-371-30)

Approx. 3 years under normal use (for series 342-451)

Length standard: Electromagnetic rotary sensor (for series 342-271-30/342-371-30)
Electrostatic capacity absolute sensor (for series 342-451)

Standard accessories:

Spanner (301336), 1 pc (except for series 342-451)

Optional accessories

Connecting cables (digital model)

1m: 05CZA662

2m: 05CZA663

USB Input Tool Direct

USB-ITN-B (2m): 06ADV380B

Connecting cables for U-WAVE-T (digital model)

02AZD790B (160mm)

For foot switch: 02AZE140B

Connecting cables (Quickmike type)

1m: 937387

2m: 965013

USB Input Tool Direct

USB-ITN-E (2m): 06ADV380E

Connecting cables for U-WAVE-T (Quickmike type)

02AZD790E 160mm

For foot switch: 02AZE140E

Refer to page B-68 for details.

Crimp Height Micrometers Series 342,112,142

- Measures the height of crimp contacts.
- Equipped with Ratchet Stop for constant measuring force.
- IP65 water/dust protection (digital model).
- Model 342-451 is the Quickmike type, which provides a speedy spindle feed of 10mm per thimble rotation, which enables widely differently sized features to be measured quickly.



Digimatic (LCD)
342-271-30

IP 65



Quickmike type (LCD)
342-451

IP 54

ABSOLUTE™



112-401

SPECIFICATIONS

Metric			
Order No.	Range	Resolution	Accuracy*
Digimatic (LCD)			
342-271-30	0 - 20mm	0.001mm	±3μm
Quickmike (LCD)			
342-451	0 - 15mm	0.001mm	±3μm

* Excluding quantizing error

Metric			
Order No.	Range	Graduation	Accuracy
Mechanical counter model			
142-402	0 - 25mm	0.01mm	±3μm
142-403	0 - 25mm	0.001mm	±3μm

Metric			
Order No.	Range	Graduation	Accuracy
Analog			
112-401	0 - 25mm	0.01mm	±3μm

Inch/Metric			
Order No.	Range	Resolution	Accuracy*
Digimatic (LCD)			
342-371-30	0 - .8"	.00005"/0.001mm	±.00015"

* Excluding quantizing error

DIMENSIONS

