RACEABILITY

RACEABILITY

PIN VISE

PLUG GAUGES

# SUB-ZERO Treatment (Cryogenic hardened) for improved durability

Use Ring Gauge as master gauge for "0" adjustment of measuring tools such as bore gauge, inside micrometer, dial caliper,



MATERIAL • Alloy tool steel


## SPECIFICATIONS

Size (mm)	Step (mm)	Out of Out of Roundness Cylinldricity $(\mu m)$ $(\mu m)$		Tolerance (μm)	Hardness (HV)
1 to less than 30	0.1 step	0.5	0.5	± 1.0	
30 to less than 50	0.1 step	0.8	0.8	± 1.5	
50 to less than 60					653
60 to less than 80	0.5 step	1.0	1.0	± 2.0	772
80 to less than 100					,,,,
100 to less than 200	5.0 step	2.0	2.0	± 5.0	

⟨Stock available size⟩

Size (mm)	Step (mm)		
1 to less than 50	0.1 step	1.0·1.1·1.2·1.3·1.4·1.5·1.6·1.7·1.8· 1.9·2.0·2.1·2.2·2.3·2.4·2.5·2.6· 2.750.0	
50 to less than 100	0.5step	50.5·51.0·51.5·52.0·52.5·53.0·53.5· 54.0·54.5·55.0·55.5·56.0·56.5·57.0· 57.5100.0	
100 to less than 200	5.0 step	105.0·110.0·115.0·120.0·125.0·130.0· 135.0·140.0·145.0·150.0·155.0·160.0· 165.0200.0	

#### DIMENSIONS



Size List

Size D (mm)	Outside Diameter d (mm)	Thickness B(mm)	Chamfering for outside diameter C (mm)	Chamfering for inside diameter F (mm)	Remarks	Weight
1 to less than 2.5	22	4	0.4	0.3		10g
2.5 to less than 5	22	5	0.4	0.5		10g
5 to less than 10	32	8	0.8	0.5	0.5 1.0 Knurled	50g
10 to less than 15	38	10				80g
15 to less than 20	45	12	1.2			100g
20 to less than 25	53	14				200g
25 to less than 32	63	16	1.5			300g
32 to less than 40	71	18				400g
40 to less than 50	85	20				600~700g
50 to less than 60	100			- 1.5		0.9~1.1kg
60 to less than 70	112		2.0			1.1~1.3kg
70 to less than 80	125	24				1.4~1.6kg
80 to less than 90	140					1.7~1.9kg
90 to less than 100	160					2.3~2.6kg
100 to less than 110	180	30	2.4			3.7~4.1kg
110 to less than 120	190	35				4.7~5.1kg
120 to less than 130	200	35				5.0~5.5kg
130 to less than 140	210	38				5.7~6.3kg
140 to less than 160	230					6.6~8.2kg
160 to less than 180	260	40		2.0		8.6~10kg
180 to less than 200	280					9.4~11kg

## **STEEL RING GAUGE SET**

## **SUB-ZERO TREATMENT (Cryogenic hardened)**



Set List		
Set No.	Nominal Size	Pieces per set
RG-1	1.0 • 1.5 • 2.0 • 2.5 • 3.0 • 4.0 • 5.0 • 6.0 • 7.0 • 8.0 • 9.0 • 10.0	12
RG-2	11.0 • 12.0 • 13.0 • 14.0 • 15.0 • 16.0 • 17.0 • 18.0 • 19.0 • 20.0 • 22.0 • 24.0	12
RG-3	25.0 · 26.0 · 27.0 · 28.0 · 30.0 · 32.0 · 34.0 · 35.0 · 36.0 · 37.0 · 38.0 · 40.0	12
RG-4	42.0 · 44.0 · 45.0 · 46.0 · 47.0 · 48.0 · 50.0	7
RG-5	52.0 · 54.0 · 55.0 · 56.0 · 58.0 · 60.0 · 65.0	7
RG-6	68.0 · 70.0 · 75.0 · 80.0	4
RG-7	85.0 • 90.0 • 95.0 • 100.0	4