



Select Language ▼

You're here:

- [Products](#) »
- [Tension Meter](#) »
- [Hand-Held, electronic](#) »
- [CTM Series](#)

Tension Meter CTM

2 Tension ranges up to 9 kN and 45 kN

Electronic wire rope tension meter to determine the tension of pretensioned, non-moving ropes, cables, wires, overhead lines, etc. up to max. 25.4 mm (1 inch) Ø.

This hand-held unit is used for control and comparison measurement of pretensioned, non running ropes.

Tension meter with large easy to read LCD display



Tension meter CTM

Special Features

- Tension meter for rope diameters from 4.75 up to 25.4 mm (3/16 up to 1 inch)
- Switchable units kN, lbf, kgf
- The reading is shown directly in the display; there is no need for comparison tables
- Large easy to read LCD display; the reading is 2.54 cm high



- Delivery includes calibration for one material. Calibrations for 20 different materials can be saved.
- RS 232 interface for data transfer to PC
- Unit with internal memory. Readings can be transferred at a later date to PC
- Automatic zero setting independent to measuring position

Standard Features

- Rugged device, designed for outdoor use
- Telescope handle
- Battery operation

Available Models

Model	Measuring Range kN	Measuring Range lbf	Measuring Range kgf
CTM-2000	9 kN	2000 lbf	900 kgf
CTM-10000	45 kN	10000 lbf	4500 kgf

Guide Rollers

Model	Rope Diameter mm	Rope Diameter inch
CTM-SH-L	4.75 - 6.35	3/16 - 1/4
CTM-SH-P	4.75 - 12.7	3/16 - 1/2
CTM-SH-S	6.35 - 19.05	1/4 - 3/4
CTM-SH-T	12.7 - 25.4	1/2 - 1

Delivery includes one roller set (as requested). Additional roller sets are optional available.

Calibration

We have a large selection of calibration samples. Please send us 3 m of the material to be measured, if our standard samples differ from your material.

To get the highest accuracy for various cable types with the same diameter (e. g. 6 mm 7x7 and 6 mm 6x19), different calibrations should be used.

Calibration Report



Calibration Certificate

Calibration certificate with calibration report is optional available.

Delivery Includes

Tension meter with carrying case including calibration for one material, roller set (as requested), operating instructions in english

Dimensions

For PDF-file please
click picture

Specifications

Accuracy:	± 3 % full scale
Measuring unit:	N, lbf, kgf switchable
Material diameter:	4.75 - 25.4 mm (3/16 - 1 inch)
Display:	LCD 2.54 cm high, full text prompts

Numbers of calibrations:	Up to 20 calibrations can be saved
Resolution:	CTM-2000: low (50 N/10 lbf/5 kgf), middle (20 N/5 lbf/2 kgf), high (10 N/2 lbf/1 N) CTM-10000: low (200 N/50 lbf/20 kgf), middle (100 N/20 lbf/10 kgf), high (50 N/10 lbf/5 kgf)
Power supply:	2 batteries, size AA
Temperature range:	-20 - 60 °C
Dimensions:	61 x 24 x 8 cm
Weight, net (gross):	Approx. 5.7 kg (approx. 9.5 kg)

Specifications subject to change without notice!

- [Contact](#) |
- [Imprint](#) |
- [Sitemap](#)

HANS SCHMIDT & CO GMBH | Schichtstraße 16 | 84478 Waldkraiburg / Germany | Tel.: + 49 (0)8638 9410-0 | Fax: + 49 (0)8638 4825