


## A12

### Mandrel Built Heavy Duty Air Hose – BSEN 2398 Class B Type 4 (BS5118/2)

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (bar)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
13	1/2	24	20	60	130	0.45	20 or 40
19	3/4	30	20	60	190	0.57	20 or 40
25	1	36	20	60	250	0.67	20 or 40
32	1.1/4	45	20	60	320	1.09	20 or 40
38	1.1/2	51	20	60	380	1.22	20 or 40
51	2	65	20	60	510	1.70	20 or 40



**Lining:** Black, NR/SBR rubber

**Reinforcement:** High strength synthetic textile yarn

**Cover:** Yellow, Black, Red, Blue weather, ozone and abrasion resistant SBR/EPDM rubber

**Branding:** Longitudinal stripe and embossed brand

**Brand legend:** Type Number/WP/BP/Bore Size

**Temperature range:** -40°C to +70°C

## A16

### Mandrel Built Steel Reinforced Air Hose – BS 5118 Type 3

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (bar)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
13	1/2	25.4	40	120	156	0.64	20 or 40
19	3/4	31.4	40	120	228	0.84	20 or 40
25	1	37.8	40	120	300	1.05	20 or 40
32	1.1/4	48.0	40	120	384	1.71	20 or 40
38	1.1/2	55.6	40	120	456	2.17	20 or 40
51	2	66.8	40	120	612	3.41	20 or 40
63	2.1/2	80.7	40	120	756	3.41	20 or 40
76	3	93.4	40	120	912	4.15	20 or 40
102	4	123.8	40	120	1224	6.87	20 or 40

**Lining:** Black, oil mist resistant Nitrile rubber

**Reinforcement:** Layers of high tensile stranded steel wire

**Cover:** Yellow, Black, Red, Blue weather, ozone and abrasion resistant SBR/EPDM rubber

**Branding:** Longitudinal stripe and embossed brand

**Brand legend:** Type Number/WP/BP/Bore Size

**Temperature range:** -40°C to +70°C

