



## F31

### Mandrel Built Brewers/Potable Water Delivery Hose

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (psi)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
13	½	26.6	20	60	130	0.60	20 or 40
19	¾	32.6	20	60	190	0.78	20 or 40
25	1	38.6	17	51	250	0.93	20 or 40
32	1.1/4	45.6	17	51	320	1.17	20 or 40
38	1.1/2	51.6	17	51	380	1.35	20 or 40
51	2	68.4	17	51	510	2.33	20 or 40
63	2.1/2	81.0	17	51	630	2.78	20 or 40
76	3	93.5	9	36	760	3.24	20 or 40
102	4	118.5	9	36	1020	4.02	20 or 40



**Lining:** Red non taint non toxic natural rubber – FDA approved ingredients

**Reinforcement:** Synthetic textile yarn

**Cover:** Orange, weather and ozone resistant EPDM rubber

**Branding:** White longitudinal stripe and embossed brand

**Brand legend:** Type Number/WP/BP/Bore Size

**Temperature range:** - 40°C to + 70°C

## F502

### Mandrel Built Brewers/Potable Water Suction & Delivery Hose

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (psi)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
38	1.1/2	55.2	20	60	304	1.82	20 or 40
51	2	68.1	20	60	408	2.43	20 or 40
63	2.1/2	80.9	17	51	504	3.06	20 or 40
76	3	97.0	17	51	608	4.37	20 or 40
102	4	118.5	17	51	816	4.57	20 or 40
152	6	175.0	17	51	1216	9.47	20 or 40

**Lining:** Red non taint non toxic natural rubber – FDA approved ingredients

**Reinforcement:** Synthetic textile yarn; double wire helix

**Cover:** Orange, weather and ozone resistant EPDM rubber

**Branding:** White longitudinal stripe and embossed brand

**Brand legend:** Type Number/WP/BP/Bore Size

**Temperature range:** - 40°C to + 70°C

