



**LEG JETTING HOSE**

**SLJ-2000-HD (2000 PSI)**

**Recommended For:** Used water delivery hose for deluge systems on offshore oil rig installations.  
**Temperature Range:** -4 °F to +179 °F (-20 °C to +82 °C)  
**Tube:** Black NR/SBR blended  
**Reinforcement:** High strength textile fabric

**Cover:** Black NR/SBR or EPDM  
**Branding:** Continuous transfer. Example: "S-SERIES CLEAN MASTER 2000 HD 2" 2000 PSI (137 BAR)"

**/// S-SERIES /// CLEAN MASTER LEG JETTING 2000 D HD 2" 2000 PSI (137 BAR)**

PRODUCT CODE	Size	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (METER)
32-SLJ-2000-HD	32	2	71	2000	4:1	61
48-SLJ-2000-HD	48	3	117	2000	4:1	61
64-SLJ-2000-HD	64	4	133	2000	4:1	61
80-SLJ-2000-HD	80	5	170	2000	4:1	61
96-SLJ-2000-HD	96	6	195	2000	4:1	61

**SLJ-3000-HD (3000 PSI)**

**Recommended For:** Used water delivery hose for deluge systems on offshore oil rig installations.  
**Temperature Range:** -4 °F to +179 °F (-20 °C to +82 °C)  
**Tube:** Black NBR Rubber  
**Reinforcement:** Spiral Steel Cable

**Cover:** Black CR Rubber  
**Branding:** Continuous transfer. Example: "S-SERIES CLEAN MASTER 3000 HD 2" 3000 PSI (206 BAR)"

**/// S-SERIES /// CLEAN MASTER LEG JETTING 3000 D HD 2" 3000 PSI (206 BAR)**

PRODUCT CODE	Size	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (METER)
32-SLJ-3000-HD	32	2	86	3000	4:1	61
40-SLJ-3000-HD	40	2-1/2	100	3000	4:1	61
48-SLJ-3000-HD	48	3	111	3000	4:1	61
64-SLJ-3000-HD	64	4	139	3000	4:1	61
80-SLJ-3000-HD	80	5	187	3000	4:1	61
96-SLJ-3000-HD	96	6	216	3000	4:1	61