



T602

Mandrel Built Oil and Fuel Suction & Delivery Hose

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (psi)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
19	¾	29.0	10	30	133	0.60	20 or 40
25	1	35.0	10	30	175	0.74	20 or 40
32	1.1/4	42.0	10	30	224	0.95	20 or 40
38	1.1/2	48.0	10	30	266	1.19	20 or 40
51	2	62.0	10	30	357	1.70	20 or 40
63	2.1/2	74.5	10	30	441	2.32	20 or 40
76	3	88.0	10	30	532	2.61	20 or 40
102	4	115.0	10	30	714	3.80	20 or 40



Lining: Black, fuel and oil resistant nitrile rubber

Reinforcement: Multiple layers of synthetic textile yarn; double steel wire helix and twin conductive copper wires

Cover: Black, oil, fuel, weather and ozone resistant Chloroprene rubber

Branding: Red spiral stripe and embossed brand

Brand legend: Type Number/WP/BP/Bore Size

Temperature range: - 35°C to + 80°C

T607

Mandrel Built Heavy Duty Oil and Fuel Suction & Delivery Hose

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (psi)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
51	2	64.5	17	51	408	1.96	40
63	2.1/2	77.5	17	51	504	2.47	40
76	3	93.5	17	68	608	3.63	40
102	4	118.0	17	68	816	4.80	40
125	5	149.0	10	40	1000	7.59	20
152	6	174.0	10	40	1216	9.36	20
203	8	230.0	10	40	1624	15.39	20

Lining: Black, fuel and oil resistant nitrile rubber

Reinforcement: Multiple layers of synthetic yarn; double steel wire helix and twin conductive copper wires

Cover: Black, oil, fuel, weather and ozone resistant Chloroprene rubber

Branding: Brown spiral stripe and embossed brand

Brand legend: Type Number/WP/BP/Bore Size

Temperature range: - 35°C to + 80°C

