



STEAM HOSE

205MB STEAM KING® (232 °C , 250 PSI)

Recommended For: All types of steam - saturated and super-heated up to 250 PSI and +450 °F (+232 °C). Special cover for oil resistance.

Temperature Range: -40 °F to +450 °F (-40 °C to +232 °C) continuous service.

Tube: Black. Type P2 (EPDM).

Reinforcement: Braided, high tensile steel wire.

Cover: Black, Type P2 (EPDM). All sizes are perforated.

Branding: Continuous transfer. Example: "S-SERIES PLANT MASTER STEAM 205 3/8" 250 PSI (17 BAR)"

CAUTION: DO NOT ALTERNATE USE BETWEEN STEAM AND WATER. TIGHTEN CLAMPS BEFORE USING.

S-SERIES PLANT MASTER STEAM 205 3/8" 250 PSI (17 BAR)

PRODUCT CODE	Size	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (METER)
6-205MB	6	3/8	20.5	261	10:1	100
8-205MB	8	1/2	24	261	10:1	100
12-205MB	12	3/4	32	261	10:1	100
16-205MB	16	1	38	261	10:1	100
24-205MB	24	1-1/2	52	261	10:1	100
32-205MB	32	2	67	261	10:1	100

SSM165-90SD (165 °C , 90 PSI)

Recommended For: Use in the chemical, petrochemical and applications requiring steam.

Temperature Range: -40 °F to +329 °F (-40 °C to +165 °C)

Tube: Black EPDM Rubber

Reinforcement: Wire braider

Cover: Black, smooth (wrapped finish) EPDM rubber, higher resistance to weather, ozone and abrasion

Branding: Continuous transfer. Example: "S-SERIES PLANT MASTER STEAM 90SD 3/8" 90 PSI (6 BAR)"

S-SERIES PLANT MASTER STEAM 90SD 3/8" 90 PSI (6 BAR)

PRODUCT CODE	Size	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (METER)
6-SSM165-90SD	6	3/8	21.5	90	10:1	100
8-SSM165-90SD	8	1/2	25	90	10:1	100
12-SSM165-90SD	12	3/4	33	90	10:1	100
16-SSM165-90SD	16	1	40	90	10:1	100
24-SSM165-90SD	24	1-1/2	54	90	10:1	30
32-SSM165-90SD	32	2	69	90	10:1	30