



S53 Mandrel Built Textile Reinforced Steam Hose – BS 5122 Class A

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (psi)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
13	½	24	7	70	130	0.37	20 or 40
19	¾	31	7	70	190	0.55	20 or 40
25	1	38	7	70	250	0.74	20 or 40
32	1.1/4	46	7	70	320	0.97	20 or 40
38	1.1/2	54	7	70	380	1.10	20 or 40
51	2	67	7	70	510	1.70	20 or 40
76	3	88	10	30	456	2.57	20 or 40



- Lining:** Black, steam resistant EPDM rubber
- Reinforcement:** Multiple layers of high strength and heat resistant synthetic yarns
- Cover:** Black / Maroon heat, weather and ozone resistant EPDM rubber
- Branding:** Longitudinal embossed stripe
- Brand legend:** Type Number/WP/BP/Bore Size
- Temperature range:** Max. +170°C

S58 Mandrel Built Superheated Steam Hose – BS 5342 Class A

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (psi)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
13	½	27	17	170	156	0.64	20 or 40
19	¾	33	17	170	228	0.81	20 or 40
25	1	42	17	170	300	1.25	20 or 40
32	1.1/4	49	17	170	384	1.62	20 or 40
38	1.1/2	55	17	170	456	1.93	20 or 40
51	2	68	17	170	612	2.68	20 or 40
63	2.1/2	80	17	170	756	3.25	20 or 40
76	3	98	17	170	912	4.99	20 or 40

- Lining:** Black, steam resistant EPDM rubber
- Reinforcement:** Multiple layers of high strength brass coated stranded steel wire
- Cover:** Black / Maroon heat, weather and abrasion resistant EPDM rubber
- Branding:** Longitudinal embossed stripe
- Brand legend:** Type Number/WP/BP/Bore Size
- Temperature range:** 235°C maximum at 17 bar WP

