




## W101

### Mandrel Built Heavy Duty Water Suction & Delivery Hose

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (psi)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
19	¾	29	10	30	114	0.58	20 or 40
25	1	35	10	30	150	0.68	20 or 40
32	1.1/4	42	10	30	192	0.89	20 or 40
38	1.1/2	48	10	30	228	1.11	20 or 40
51	2	61	10	30	306	1.51	20 or 40
63	2.1/2	74	10	30	378	1.85	20 or 40
76	3	88	10	30	456	2.57	20 or 40
102	4	115	10	30	612	3.72	20 or 40
127	5	146	10	30	762	6.56	40
152	6	171	10	30	912	8.36	40
203	8	225	10	30	1218	13.32	40



**Lining:** Black, NR/SBR rubber

**Reinforcement:** Synthetic textile and steel wire helix embedded between layers

**Cover:** Black, weather and abrasion resistant SBR/EPDM rubber

**Branding:** Yellow spiral stripe and longitudinal embossed brand

**Brand legend:** Type Number/WP/BP/Bore Size

**Temperature range:** -40°C to +70°C

## W22

### Mandrel Built Heavy Duty Water Delivery Hose – BS 5119 Type A

ID (mm)	ID (in)	OD (mm)	WP (bar)	BP (psi)	Min Bend Radius (mm)	Weight (kg/m)	Unit Length (m)
13	½	22	10	30	130	0.35	20 or 40
19	¾	28	10	30	190	0.45	20 or 40
25	1	34	10	30	250	0.57	20 or 40
32	1.1/4	41	10	30	320	0.74	20 or 40
38	1.1/2	51	10	30	380	1.23	20 or 40
51	2	61	10	30	510	1.22	20 or 40
63	2.1/2	77	10	30	630	2.06	20 or 40
76	3	90	10	30	760	2.48	20 or 40
102	4	116	10	30	1020	3.48	20 or 40
127	5	142	10	30	1270	4.28	40
152	6	168	10	30	1520	5.31	40

**Lining:** Black, NR/SBR rubber

**Reinforcement:** Synthetic textile

**Cover:** Black, weather and abrasion resistant SBR/EPDM rubber

**Branding:** Blue spiral stripe and longitudinal embossed brand

**Brand legend:** Type Number/WP/BP/Bore Size

**Temperature range:** -40°C to +70°C

